



FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



ITER

der entscheidende Schritt zum Fusionsreaktor

G. Janeschitz

**Leiter Programm Fusion
Forschungszentrum Karlsruhe**




Fusion


die Energiequelle der Sonne
muss auf der Erde nutzbar
gemacht werden



Schematic View of a Fusion Power Reactor



- A Tokamak-Halle
- B Tritiumrückführung
Brennstoffeinspeisung
- C Neutralteilchen-Strahl
- D Turbinenhalle
- E Energieversorgung
- F Kryopflanze
- G Notstrom-Versorgung






ITER is not a reactor but it is an experiment with a reactor plasma

Outline


- **Fusion Basics**
- **How to size a reactor class machine**
- **ITER history and objectives**
- **ITERs design, technology and R&D**
- **The Challenges ahead and conclusions**



For Fusion to happen the Coulomb Barrier has to be overcome




- Needs kinetic energy
- Could be provided by temperature






Die wichtigsten Fusionsreaktionen




Abkürzungen

D	Deuterium
T	Tritium
He	Helium
B	Bor
p	Proton

Reaktionen




Optimal ist die **Deuterium/Tritium-Reaktion** bei etwa 100 Millionen Grad Plasmatemperatur





Tritium muss erbrütet werden



Tritium ist radioaktiv. Wegen der Halbwertszeit von nur 12 Jahren ist es in der Natur nicht ausreichend vorhanden. Tritium muss deshalb künstlich aus Lithium hergestellt („erbrütet“) werden.

➡ Die Rohstoffe der Fusion sind Deuterium und Lithium





Fusion ist eine sichere abfallarme nukleare Energiequelle


- Bei derzeitigem Weltenergieverbrauch hat die Fusion eine Reichweite von etwa 30 Millionen Jahren => praktisch unbegrenzte Energieversorgung
- Deuterium und Lithium (Brennstoff) sind aus den Weltmeeren zu gewinnen (Lithium auch aus Sanden) und daher für Jedermann zugänglich
- Fusionsreaktoren werden mit He Gas gekühlt (Austrittstemperaturen von 550 - 900 °C) und somit auch geeignet für die Herstellung von Wasserstoff
- **Da das Fusionsprodukt He ist, fällt primär kein radioaktiver Abfall an**
 - Allerdings wird durch die bei der Fusion entstehenden Neutronen die Struktur des Reaktors radioaktiv
 - Materialien mit kurzen Abklingzeiten ~ 200 Jahre vermeiden Endlager




FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION




Lorenz force attaches charged particles to fieldlines
-> magnetic Confinement



Toroidal magnetic
Confinement
Configuration
requires
Helical Fieldlines


Magnetic Confinement

Plasmaeinschluß durch Magnetfelder





Magnetic Confinement, The Tokamak Principle






FUSION


Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



The Plasma of a modern Divertor Tokamak







FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft


FZK - EURATOM ASSOCIATION



Plasma Operation in JET




Remote Handling in JET





Verfahren zum Aufheizen eines Tokamakplasmas






Turbulence driven Energy Loss

Turbulent energy transport sets in at a critical temperature gradient which depends on the local temperature

Radial size of turbulent structures can be reduced by ExB shear and by magnetic shear



Tripple Product Diagramm

How do we size a Reactor
class Fusion machine (1)

- **$T_i > 10 \text{ keV}$** -> (to optimise D-T reaction rate)
 - $\Rightarrow n_e \times \tau_E \sim 6.0 \cdot 10^{20} \text{ m}^{-3}\text{s}$
 - $\Rightarrow n_e \sim 1.0 \cdot 10^{20} \text{ m}^{-3}$ -> (close to Density Limit: $n_L \sim I/a^2\pi$)
 - $\Rightarrow \tau_E \sim 6.0 \text{ s}$ -> (defines more or less machine size)

H-mode Confinement Scaling Relation:

$$\tau_{E,th}^{ELMy} = 0.0562 \times I^{0.93} B^{0.15} P^{-0.69} n_{e,19}^{0.41} M^{0.19} R^{1.97} \varepsilon^{0.58} \kappa^{0.78}$$




How do we size a Reactor class Fusion machine (2)

All of the above mentioned physics and engineering constraints are combined in a

“System Code”

which is able to calculate a consistent parameter set.





The ITER Machine

Doughnut-Shaped Plasma

- V: 840m^3

R/a: $6.2\text{m} / 2\text{m}$

Vertical elongation: 1.85

Triangularity: 0.45


- Density: 10^{20}m^{-3}

- Peak Temperature: 17keV

- Fusion Power: 500MW

- Plasma Current : 15MA

- Toroidal field: 5.4T





ITER History

- **1988-1991 - (CDA) Conceptual Design Phase**
 - Start of common activities among EU, RF, USA and JA
 - Selection of machine parameters and objectives
- **1992-1998 - (EDA) Engineering Design Phase**
 - Developed design capable of ignition - large and expensive
 - The Parties (EU, JA, RF, US) endorsed design but could not afford to build it
- **1999 – 2001 – (EDA continues)**
 - US withdraws from project
 - Remaining Parties searched for less ambitious goal
 - New design: moderate plasma power amplification at about half the cost.
- **2001 - now (CTA and ITA)**
 - End of EDA and start of negotiations on construction and operation
 - 4 site offers. In 2003 US re-joins, China & South Korea are accepted as full partners.
 - **Cadarache selected as ITER site in June 2005**
 - India Joins in Dec 2005





ITERs Technical Objectives

- **Q (ratio of fusion power to auxiliary heating power) ≥ 10 (>5 in steady state). Possibility of controlled ignition.**
 - **Power flat top 300 s up to steady state.**
 - **Flexible operation range, with access to advanced modes.**
 - Integrate the technologies essential for a fusion reactor (e.g. superconducting magnets, remote maintenance);
 - Test components for a future reactor (e.g. divertor and torus vacuum pumps, tritium breeding blanket modules).
 - Average neutron flux $> 0.5 \text{ MW/m}^2$, fluence $> 0.3 \text{ MWa/m}^2$
 - Possible later installation of tritium breeding blanket.
 - **Operate for ~ 20 years, using externally supplied tritium.**
- ITER is the first Reactor Plasma – its performance will determine the fate of fusion as an energy source**
- ITER has to exceed its nominal performance by $> 50\%$ in order to warrant the construction of a DEMO reactor**
- See also talk of Prof Wolf today !!**




FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



Main Features of the ITER Design



Direct Construction Cost
~ 4 billion €

Licensing/Construction
9 years


Operation
20 years
~ 250 million
Euro/year

International
Organization
600 staff
Visiting researchers

Staffing Cost ~ 1 billion €
for first 10 years

ITER Site

Cadarache France






FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



Tokamak Building Complex



Assembly Area

Tokamak

Hot Cell

copyright 2005 ITER-project illustration: Eric Reinkens, www.kernkraftwelt.at



FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



The ITER Design and Technology has been underpinned by R&D


CENTRAL SOLENOID MODEL COIL



Radius 3.5 m
Height 2.8m
 $B_{\max} = 13$ T
 $W = 640$ MJ
0.6 T/sec

Completed R&D Activities by July 2001.

VACUUM VESSEL SECTOR




Double-Wall, Tolerance ± 5 mm

BLANKET MODULE



HIP Joining Tech
Size : 1.6 m x 0.93 m x 0.35 m

REMOTE MAINTENANCE OF DIVERTOR CASSETTE



Attachment Tolerance ± 2 mm

REMOTE MAINTENANCE OF BLANKET




4 t Blanket Sector
Attachment Tolerance ± 0.25 mm

TOROIDAL FIELD MODEL COIL



Height 4 m
Width 3 m
 $B_{\max} = 7.8$ T
 $I_{\max} = 80$ kA

DIVERTOR CASSETTE



Heat Flux >15 MW/m², CFC/W






FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION

ITER Toroidal Field Magnets







FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION




ITER-FEAT coil assembly







ITER Model Coil, High Temperatur SC Current Leads



Toska Facility

ITER Model Coil

HTS Current
Lead



FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



The ITER Design and Technology has been underpinned by R&D


CENTRAL SOLENOID MODEL COIL



Radius 3.5 m
Height 2.8m
 $B_{\max} = 13 \text{ T}$
 $W = 640 \text{ MJ}$
 0.6 T/sec

Completed R&D Activities by July 2001.

VACUUM VESSEL SECTOR




Double-Wall, Tolerance $\pm 5 \text{ mm}$

BLANKET MODULE



HIP Joining Tech
Size : 1.6 m x 0.93 m x 0.35 m

REMOTE MAINTENANCE OF DIVERTOR CASSETTE



Attachment Tolerance $\pm 2 \text{ mm}$

REMOTE MAINTENANCE OF BLANKET




4 t Blanket Sector
Attachment Tolerance $\pm 0.25 \text{ mm}$

TOROIDAL FIELD MODEL COIL



Height 4 m
Width 3 m
 $B_{\max} = 7.8 \text{ T}$
 $I_{\max} = 80 \text{ kA}$

DIVERTOR CASSETTE



Heat Flux $> 15 \text{ MW/m}^2$, CFC/W




Structure of the CS Model Coil

CS Insert Coil
(JA)



Inner Module
(US)

Outer Module
(JA)



Winding
Structure

Conductor
Structure





CS Model Coil R&D

Max. field 13.5T, max. current 46kA, stored energy 640MJ (max. in Nb₃Sn)

Ramp-up 1.2T/s (goal 0.4) and rampdown rates of -1.5T/s (goal -1.2) in insert coils, and 10,000 cycle test.



**CS Insert
Coil
(JA)**



**Inner
Module
(US)**



**Outer
Module
(JA)**



FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



CS Model Coil R&D

Closing of the Test Cryostat (JA)





FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



The ITER Design and Technology has been underpinned by R&D


CENTRAL SOLENOID MODEL COIL



Radius 3.5 m
Height 2.8m
 $B_{\max} = 13 \text{ T}$
 $W = 640 \text{ MJ}$
 0.6 T/sec

Completed R&D Activities by July 2001.

VACUUM VESSEL SECTOR




Double-Wall, Tolerance $\pm 5 \text{ mm}$

BLANKET MODULE



HIP Joining Tech
Size : 1.6 m x 0.93 m x 0.35 m

REMOTE MAINTENANCE OF DIVERTOR CASSETTE



Attachment Tolerance $\pm 2 \text{ mm}$

REMOTE MAINTENANCE OF BLANKET




4 t Blanket Sector
Attachment Tolerance $\pm 0.25 \text{ mm}$

TOROIDAL FIELD MODEL COIL



Height 4 m
Width 3 m
 $B_{\max} = 7.8 \text{ T}$
 $I_{\max} = 80 \text{ kA}$


DIVERTOR CASSETTE



Heat Flux $> 15 \text{ MW/m}^2$, CFC/W





Vacuum Vessel & In-Vessel Components




- Double-walled vacuum vessel lined by modular removable components,
- blanket modules, divertor cassettes, and diagnostics sensors, as well as port plugs for limiters, heating antennae, diagnostics and test blanket modules.
- The total vessel/in-vessel mass is **~10,000 t**.
- Components absorb most of the radiated heat from the plasma and protect the magnet coils from excessive nuclear radiation.
- **The VV is able to remove the decay heat from all in Vessel components in case of coolant failure**
- A tight fitting configuration of the VV to the plasma aids passive plasma vertical stability
- ferromagnetic material “inserts” in the VV reduce toroidal field ripple and its associated particle losses.



ITER Vacuum Vessel

Full Scale Sector Model
(1/20 of full torus)

Sector-B (1/2 Sector)



Sector-A (1/2 Sector)

Dimensional accuracy after welding sector halves ± 3 mm



FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



The ITER Design and Technology has been underpinned by R&D


CENTRAL SOLENOID MODEL COIL



Radius 3.5 m
Height 2.8m
 $B_{\max} = 13 \text{ T}$
 $W = 640 \text{ MJ}$
 0.6 T/sec

Completed R&D Activities by July 2001.

VACUUM VESSEL SECTOR




Double-Wall, Tolerance $\pm 5 \text{ mm}$

BLANKET MODULE



HIP Joining Tech
Size : 1.6 m x 0.93 m x 0.35 m

REMOTE MAINTENANCE OF DIVERTOR CASSETTE



Attachment Tolerance $\pm 2 \text{ mm}$

REMOTE MAINTENANCE OF BLANKET




4 t Blanket Sector
Attachment Tolerance $\pm 0.25 \text{ mm}$

TOROIDAL FIELD MODEL COIL



Height 4 m
Width 3 m
 $B_{\max} = 7.8 \text{ T}$
 $I_{\max} = 80 \text{ kA}$

DIVERTOR CASSETTE





Heat Flux $> 15 \text{ MW/m}^2$, CFC/W



Blanket Attachment and Manifold

- 421 blanket modules with detachable faceted first wall (FW) with Be armour on a water-cooled copper substrate, attached to a SS shielding block - minimises radioactive waste and allows testing of alternative wall materials.



- Initial blanket acts solely as a neutron shield,
- tritium breeding experiments are carried out on test blanket modules inserted and withdrawn at radial equatorial ports.
- About 4t per module.




FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



Blanket Module R&D



Drilling of forged steel block
(Shield block cooling channels)



Bending of ice-plugged steel block
(10,000 ton press machine)



Steel block after solution heat treatment
(1010-1054 °C)



Assembly of steel tubes and DS Cu plates



Final assembly of FW and shield block



Canning for HIPing



FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



The ITER Design and Technology has been underpinned by R&D


CENTRAL SOLENOID MODEL COIL



Radius 3.5 m
Height 2.8m
 $B_{\max} = 13 \text{ T}$
 $W = 640 \text{ MJ}$
 0.6 T/sec

Completed R&D Activities by July 2001.

VACUUM VESSEL SECTOR




Double-Wall, Tolerance $\pm 5 \text{ mm}$

BLANKET MODULE



HIP Joining Tech
Size : 1.6 m x 0.93 m x 0.35 m

REMOTE MAINTENANCE OF DIVERTOR CASSETTE



Attachment Tolerance $\pm 2 \text{ mm}$

REMOTE MAINTENANCE OF BLANKET




4 t Blanket Sector
Attachment Tolerance $\pm 0.25 \text{ mm}$

TOROIDAL FIELD MODEL COIL



Height 4 m
Width 3 m
 $B_{\max} = 7.8 \text{ T}$
 $I_{\max} = 80 \text{ kA}$

DIVERTOR CASSETTE




Heat Flux $> 15 \text{ MW/m}^2$, CFC/W




Divertor - Design

- 54 cassettes.
- Large openings between the inner and outer divertor balance heat loads in the inboard and outboard channels.



Vertical target (C part)

Transparent liner for pumping



➤ Design uses C at the vertical target strike points.

➤ W is the backup.

➤ The targets are replaceable in the Hot Cell.



FUSION


Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



Divertor Prototypical Vertical Target and cassette Mock-ups

- Under high heat flux testing in the Le Creusot e-beam facility, it sustained:
 - **1000 cycles at 18 MW.m⁻² on the W macro-brush armour**
 - **2000 cycles at 20 MW.m⁻² on the CfC armour.**
 - **Finally, the CfC armour was shown to survive > 30 MW.m⁻² in a CHF test.**





FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



The ITER Design and Technology has been underpinned by R&D


CENTRAL SOLENOID MODEL COIL



Radius 3.5 m
Height 2.8m
 $B_{\max} = 13 \text{ T}$
 $W = 640 \text{ MJ}$
 0.6 T/sec

Completed R&D Activities by July 2001.

VACUUM VESSEL SECTOR




Double-Wall, Tolerance $\pm 5 \text{ mm}$

BLANKET MODULE



HIP Joining Tech
Size : 1.6 m x 0.93 m x 0.35 m

REMOTE MAINTENANCE OF DIVERTOR CASSETTE



Attachment Tolerance $\pm 2 \text{ mm}$

REMOTE MAINTENANCE OF BLANKET




4 t Blanket Sector
Attachment Tolerance $\pm 0.25 \text{ mm}$

TOROIDAL FIELD MODEL COIL



Height 4 m
Width 3 m
 $B_{\max} = 7.8 \text{ T}$
 $I_{\max} = 80 \text{ kA}$


DIVERTOR CASSETTE



Heat Flux $> 15 \text{ MW/m}^2$, CFC/W



Remote Maintenance of the Divertor - cassette toroidal and radial mover



Divertor Remote Handling Test Platform


Central
Cassette Carrier

Divertor Port

Plug Handling
Vehicle

Dummy
Cassette

Toroidal Mover





FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



The ITER Design and Technology has been underpinned by R&D


CENTRAL SOLENOID MODEL COIL



Radius 3.5 m
Height 2.8m
 $B_{\max} = 13 \text{ T}$
 $W = 640 \text{ MJ}$
 0.6 T/sec

Completed R&D Activities by July 2001.

VACUUM VESSEL SECTOR




Double-Wall, Tolerance $\pm 5 \text{ mm}$

BLANKET MODULE



HIP Joining Tech
Size : 1.6 m x 0.93 m x 0.35 m

REMOTE MAINTENANCE OF DIVERTOR CASSETTE



Attachment Tolerance $\pm 2 \text{ mm}$

REMOTE MAINTENANCE OF BLANKET




4 t Blanket Sector
Attachment Tolerance $\pm 0.25 \text{ mm}$

TOROIDAL FIELD MODEL COIL



Height 4 m
Width 3 m
 $B_{\max} = 7.8 \text{ T}$
 $I_{\max} = 80 \text{ kA}$


DIVERTOR CASSETTE



Heat Flux $> 15 \text{ MW/m}^2$, CFC/W



In Vessel Transporter for Blanket Maintenance



In-Vessel Transporter (IVT)
(Rail Mounted Vehicle System)



12/APR/00

YMO —

R&D

Vehicle Manipulator System for Blanket Maintenance

Payload~4 ton, Arm length~6m



Demonstration of

- Blanket module handling
- Rail deployment

Positioning 0.5 mm and 0.1°, rail deployed 90° around torus in ~ 30 min..



Engineering/Technology Challenges ahead



The above R&D performed during the EDA has shown the feasibility to built ITER, but now reliable functioning components have to be built !!

- ITER has millions of parts with very complex interfaces and ensuing knock-on effects
 - Unprecedented size of the super-conducting magnet and structures.
 - All in vessel components (Divertor, Blanket) are subject to large heat fluxes and electromagnetic forces
 - All maintenance operations inside the ITER machine and the refurbishment of components in the Hot Cell has to be performed remotely
- ➔ A difficult engineering and contract follow-up job lies in front of the future ITER International Team**



Organisation Challenges (1)

- The Parties contribute components “In-Kind”
 - Involve all the Parties in key fusion technology areas.
 - Share the cost of the device by ‘value’ and not by currency.
 - Automatically ensure fair return
- Sharing: 5/11 EU (1/11 procured in Japan), 1/11 Others. (of which 10% centrally funded and 90% in-kind)






FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION




Procurement Sharing





Organisation Challenges (2)

- Forging one coherent project team across multiple cultures (and time zones) with industrial support.





Negotiation Status

- **ITER Parties are now in the process of finalising the Joint Implementation Agreement and its main instruments.**
 - **Main Agreement Text**
 - **Staffing regulations**
 - **Procurement and cost sharing**
 - **Intellectual Property Rights**
 - **Principles of Operation Programme**
 - **Resource Management**
 - **Principles on management**

- **The negotiations are successfully finished !**

To be performed in the near future:

- **Spring 2006: Ministerial Meeting to “initial” Agreement**
- **Jun-Jul 2006: Agreement Formal Signature**
- **End 2006: Agreement enters into force**






FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

ASSOCIATION



Schedule





FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATOM ASSOCIATION



Strategy for achieving commercial fusion power, The Fast Track

Plasma physics

Tokamak physics (ASDEX-UP, JET)

Concept improvements, Stellarator

Facilities

ITER

14 MeV neutron source

DEMO and PROTO combined

DEMO

PROTO

Technology


ITER-relevant technology

Fusion power technology – DEMO-relevant

Decision point

Experimental
electrical
power
production

commercial
fusion power





Conclusions

- ITER is one of the most technologically, organisationally and politically challenging projects being undertaken today.
- Nevertheless, a convincing design has been and continues to be developed able to meet its objectives, and the international infrastructure and the organisation necessary to build it on the expected timescale is (imminently) ready to be set up.
- ITER will be the proving ground for the key technologies necessary to make magnetic fusion into a viable energy source.
- The design phase has demonstrated the desirability of jointly implementing ITER in a broad-based international collaborative frame with the strong involvement of Industry.
- Procurement is split among the ITER Parties, but Europe provides 36% of the hardware. This allows considerable opportunities for European manufacturers and service providers.
- In its host role, Europe is well-placed to gain essential know-how from its involvement in most systems, via installation and plant licensing.



FUSION

Forschungszentrum Karlsruhe
in der Helmholtz-Gemeinschaft

FZK - EURATO



Energy Conversion
Technology

H₂ Production ?


IFMIF

Materials


Technology

now


Physics &
Technology



TBM, TDM



EU DEMO 2035



ITER 2016



What can ITER show about fusion safety?

- Fusion offers a safe, long term source of energy with abundant resources and major environmental advantages. Magnetic fusion has favourable safety characteristics:
 - The nuclear fusion reaction is self-limiting, bounded by the plasma pressure of the burning plasma, thus runaway does not exist.
 - Fusion power density and radioactive decay heat densities are moderate, and fast-acting emergency cooling systems are not required.
 - The ultimate performance of fusion reactor confinement barriers needs to provide about a factor 10 reduction for tritium. By comparison, fission reactors need to provide a factor 10^6 - 10^7 reduction for iodine and rare gases.
 - Structural materials are activated by fusion neutrons. With the successful development of appropriate materials, the wastes would not require isolation beyond a few hundred years.
- ITER has the main characteristics of a fusion power plant (size, power, radioactive inventories).
- Safe operation of ITER will demonstrate fusion's safety and environmental potential.